Effect 3

Two-way passive surround system

features

- Two-way passive design
- Full-range sound from compact enclosure
- Simple to install
- ▶ 90° x 90° circular waveguide

applications

- Full-range surround sound applications
- For small to medium cinemas




The Effect 3 is a two-way passive cinema surround system, designed to produce smooth, full-range surround sound. It may be installed in large-scale prestige cinemas or used for smaller multiplex cinema applications.

technical specifications

TYPE	Two-way passive, reflex enclosure
FREQUENCY RESPONSE (I)	80Hz-20kHz ±3dB
LOW FREQUENCY LIMIT	-10dB @ 50Hz
DRIVERS	8" (200mm) bass-mid driver
	I" (25mm) dome tweeter on waveguide
RATED POWER (2)	100W AES, 400W peak
RECOMMENDED AMPLIFIER	75-150W into 8 ohms
SENSITIVITY (3)	91dB Watt/1 metre
MAXIMUM SPL (4)	109dB continuous, 115dB peak
IMPEDANCE	8 ohms nominal
DISPERSION (-6dB)	90° horizontal, 90° vertical
CROSSOVER	2.5kHz passive
ENCLOSURE	24 litre (0.75cu foot) particle board construction
FINISH	Black texture
PROTECTIVE	Black acoustically transparent cloth grille
GRILLE	, ,
CONNECTORS	2-way binding posts
FITTINGS	4 x M4 teenuts on rear for 'keyhole' brackets
	2 x keyhole plates
	2 x M8 threaded inserts for wall bracket
	I x wall bracket (optional)
DIMENSIONS	(W) 445mm x (H) 465mm x (D) 245mm
	(W) 17.5ins x (H) 18.3ins x (D) 9.7ins
WEIGHT	13.0kg (27lbs)
	• · · /

overall dimensions





EFFECT 3

Century Point, Halifax Road, Cressex Business Park, High Wycombe, Buckinghamshire HP12 3SL, England. Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669 E-mail: info@martin-audio.com All information is Copyright © 2003 Martin Audio Ltd.

